



◆ SPECIFICATION

Model NO.	LBCKSHE	LBCKSSV
<b>Camera</b>		
CCD/CMOS	1/3" SONY CCD	
Image Sensor	CXD4141GG	CXD4151GG
DSP	Effio-E	UTC Effio-V
Horizontal Resolution	700TV Line	720TV Line
Effective Pixels	976(H)×582(V)	
TV System	PAL/NTSC	
Electronic Shutter Time	Auto: PAL 1/50-1/100, 000Sec; NTSC 1/60-1/100, 000Sec	
Sync System	Internal	
Usable Illumination	0.001Lux/F2.0	0.001Lux/F2.0
S/N Ratio	≥52dB	
Gamma Correction	0.45	
Scanning System	PAL: 625 Lines, 50 Field/Sec; NTSC: 525 Lines, 60 Field/Sec	
Video Output	Composite Signal (1.0Vp-p, 75Ω)	
<b>Lens</b>		
Focus Length	CS 12mm (4/6/8/16mm optional)	
Focus Control	Fixed	
Lens Type	Fixed	
Pixels	2M Pixels	
Auto Iris Support	NO	
<b>Camera Features</b>		
Day/Night	Color/ B&W	
OSD Menu Language	CN, EN, FR, DE, JP, ES, PT, RU	
Defog	NO	YES
Sense-up	NO	YES
Smart-IR	YES	NO
Wide Dynamic Range	Real WDR	DWDR
Backlight Compensation	YES	
White Balance	AUTO	
Gain Control	AUTO	
Noise Reduction	3D NR	2D NR
Privacy Masking	YES	
Digital Zoom	NO	YES
Picture Adjustment	YES	
UTC Support	YES	
<b>General</b>		
Weatherproof Housing	NO	
Anti-cut Bracket	NO, Without Bracket	
Dual Voltage	NO	
IR Cut Filter	NO	
Heater	NO	
Operation Temperature	-10°C ~ +50°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%, 300mA	
Dimension	110(W) x 45(H) x 55(D)mm	
Weight	400g	