

1430



Tally
DASCOM

Tally DASCOM's 1430 flat-bed serial dot matrix printer, is a 24 pin, 106 column printer with USB and parallel interfaces as standard. The printer is ideal for front office applications in retail outlets, travel agents, train stations and doctor's surgeries where a wide range of media is used.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1430 is ideal for counter-top printing applications such as, tickets, receipts, forms and multi-part documents.

Highlights at a glance:

- Wide carriage 24-pin flat-bed printer
- Print speeds up to 600 characters per second
- Ideal for front office applications
- Flexible media handling
- Auto switching USB and parallel interface
- Long life ribbon

The long life ribbon of the 1430 means fewer ribbon changes, less downtime and lower running costs.

With print speeds of 600 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1430 is a reliable and easy to use printer, with low running costs and flexible paper management.

Available Configuration:

- **1430** Standard Product

1430

Print Speed	600 cps (Fastest Mode); 450 cps (HS Draft), 300 cps (Draft), 100 cps (LQ) at 10 cpi
Print Method	106 column - Flat-Bed Serial Impact Dot Matrix
Resolution	Up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 cpi, Proportional Spacing
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 Million Strokes per pin
Memory	68 KB
Standard Connectivity	USB 2.0 and parallel (Bi-directional)
Standard Emulation	Epson (ESC P/2), IBM 2390 Plus
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
Consumables	Black Ribbon: 7 million characters
Standard Paper Handling	Friction and push tractor
Number of Copies	1 Original + 7 (8-part forms)
Paper Type	Cut sheet and continuous forms
Paper Weight	52 - 157 gsm
Paper Size	56 - 305 mm
Physical Weight	7.5 kg
Physical Size	495 x 342 x 202 mm (W x D x H)
Power Voltage	120 V and 220 V models available
Power Consumption	<3.5 W (Stand-By)
MTBF	10,000 hours
Drivers	Windows 98/2000/XP/Vista/7/8 and Server 2003/2008
Temperature	5° C to +35° C
Humidity	10% to 80% (not condensing)
Acoustic	< 55 dB(A) (ISO 7779)
Standard Warranty	One year with Printhead inclusive
Note	For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM AP Pte. Ltd.

21 Bukit Batok Crescent
 #29-81 WCEGA Tower
 Singapore 658065
 Tel: +65 6760 8833
 Fax: +65 6760 1066

www.dascom.com.sg

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 