

T2250



Tally

The T2250 is highly featured, reliable and stylish machines Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

Highlights at a glance:

- Print speeds up to 1200 cps
- 26,000 pages per month workload
- 136 columns
- 24 pin print head produces excellent print quality
- Automatic gap adjustment and quick tear
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Available Configuration:

- **T2250** Standard Product
- **T2250 IGP** with IGP/PJL support

T2250

Print Sped	1200 cps (Fastest Mode); 600 cps (Draft), 270 cps (DPQ), 180 cps (NLQ), 90 (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	482 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	400 million characters
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Serial RS232
Optional Connectivity	Serial Current Loop (20mA), Ethernet 10/100BaseT
Standard Emulations	IBM ProPrinter XL24, Epson LQ2550, MTPL + Barcode + LCP IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Optional Emulations	DEC LA 75, ECMA 9011, Eastern Europe, MT50
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and Large Character Printing (LCP)
Consumables	Ribbon: 5 million characters
Standard Paper Handling	Push tractors with paper parking and automatic gap adjustment (AGA).
Optional Paper Handling	Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder.
Number of Copies	Push tractor front: 1 Original + 5 copies; Push tractor rear: 1 Original + 5 copies; Single sheet: 1 Original + 5 copies
Paper Type	Continuous forms, single sheets
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 - 419 mm ; Length: 76 - 584 mm
Physical Weight	15.5 kg
Physical Size	600 x 399 x 300 mm (W x D x H)
Noise Level (ISO 7779)	53 dB(A)
Power Voltage	120 V or 230 V (selectable)
Power Consumption	40 Watt printing; <10 W Sleep Mode
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Print Volume	26,000 pages per month
MTBF	10,000 hours
Standard Warranty	One year with Printhead inclusive
Printer Drivers	Windows 2000/XP/Vista/7/8; Windows Server 2003/2008

DASCOM AP Pte. Ltd.

21 Bukit Batok Crescent
#29-81 WCEGA Tower
Singapore 658065
Tel: +65 6760 8833
Fax: +65 6760 1066

www.dascom.com.sg

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 