

## T2280+



*Tally*

The T2280+ is undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just printers, reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

### Highlights at a glance:

- Print speeds up to 1333 cps
- Full range of automatic features minimising operator intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS
- Straight through paper path for easy forms loading

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2280+ printer is the first high speed matrix printers to incorporate Ethernet on-board.

#### Available Configuration:

- **T2280+** Standard Product
- **T2280+ 2T** with additional rear tractor

## T2280+

<b>Print Speed</b>	1,333 cps (Fastest Mode); 800 cps (HS Draft), 667 cps (DQ), 222 cps (NLQ), 111 cps (LQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	680 pages per hour
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	500 million strokes per wire
<b>Memory</b>	128 KB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and Ethernet 10/100 BaseT
<b>Optional Connectivity</b>	RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS
<b>Standard Emulations</b>	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP, Genicom ANSI
<b>Optional Emulations</b>	ECAM 9014, MT460D, MT50, IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
<b>Consumables</b>	Ribbon: 20 million characters
<b>Standard Paper Handling</b>	Push tractor for continuous paper with straight paper path, 2nd rear push tractor (T2280-2T model) tear off and park position
<b>Optional Paper Handling</b>	Additional push tractor (front), Automatic cutting device
<b>Number of Copies</b>	Original + 5 copies
<b>Paper Type</b>	Continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 76 - 419 mm; Length: 76 - 559 mm
<b>Physical Weight</b>	19 kg
<b>Physical Size</b>	622 x 432 x 279 mm (W x D x H)
<b>Acoustic</b>	57 dB(A)
<b>Power Voltage</b>	120 V or 230 V (selectable)
<b>Power Consumption</b>	75 Watt Printing
<b>Temperature</b>	+10° to +35° C; 20% to 80% humidity (not condensing)
<b>Workload</b>	50,000 pages per month
<b>MTBF</b>	10,000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7/8 and Server 2003/2008; SAP
<b>Standard Warranty</b>	One year with Printhead inclusive
<b>Note</b>	For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

### DASCOM AP Pte. Ltd.

21 Bukit Batok Crescent  
#29-81 WCEGA Tower  
Singapore 658065  
Tel: +65 6760 8833  
Fax: +65 6760 1066  
www.dascom.com.sg

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 